

TETR4D



SPECIFICATION

MODEL	TETR4D
CARRYING CAPACITY	35,000kg
CUBIC CAPACITY	45m ³ Silage 70m ³
BODY	9000 x 2900 x 1900mm
AXLES	Four 150mm BPW axles, 10 stud, 420x180 brakes, Steering front and rear axles
SUSPENSION	Air suspension or Steel suspension
TYRES	560/60Rx22.5 or 600/55Rx26.5
TIPPING MECHANISM	Single 7 stage tipping ram

OPTIONAL EXTRAS

On Board weigh cell system, Automatic Lubrication system
Stainless Steel light bar on back door, Silage Sides, Hydraulic Flip
Cover system, Central Tyre Inflation System.



STANDARD FEATURES

Trailers shotblasted & finished in with two pack polyurethane Flexi Paint

Hydraulic rear door

Front grille lined with Perspex

Fast tow trailer fitted with air braking, ABS and load sensing valve

6 tonne K80 spoon hitch

Mud flaps front of trailer, front of wings and rear of trailer

Galvanised inspection ladder

Hydraulic jack leg

Sprung drawbar

LED commercial road lighting system

Side marker lights function as indicators

Rear light guards

LED flashing warning light with on/off switch

Wheel nut indicators

Conspicuity tape around body

Colour coded hydraulic hose grips