

STEWART

**BIGGER
STRONGER
TOUGHER**

VT5500



ABOUT THE VT 5500

The trailer has a flat bed 5500mm long and 2700mm wide; the body width allows two rows of bales to be carried comfortably. There is a fixed headboard with the option to add a harvest ladder. The trailer is supplied with dirt sides and a silage bin.

The flat bed and removeable gravel sides are constructed from Hardox. The 750mm high dirt sides have a hydraulic rear door with a clearance of 1950mm from the trailer floor.

The silage bin can be lifted on and off the trailer easily; it is secured with bolts onto the flat bed. The 2250mm deep silage bin, with its own hydraulic door, features a blow board for grass and a front grille for easy visibility from the tractor seat.

The trailer is fitted with a sprung drawbar with a swivel hitch eye and a jack leg. The radial flotation tyres give good performance on and off road.

The **VT 5500** also includes the same standard features as the other Stewart Trailer ranges: Granning 125mm diameter 10 stud axles, 10 stud fully welded high speed wheel rims, Granning mechanical suspension, hydraulic braking system, mud flaps, LED commercial road lighting system, LED flashing warning light, galvanised rear light guards, ratchet style park brake, chrome plated tipping rams, conspicuity tape around body, colour coded hydraulic hose grips, trailer is shotblasted then finished with two pack polyurethane Flexi Paint.

SPECIFICATION

Carrying Capacity	16,000kg
Flat Body	5500x2700mm with 4mm Hardox Floor
Dirt Sides	750mm Hardox Sides with up and over hydraulic door
Silage Bin	3mm mild steel, 2250mm high with 300mm blow board & hydraulic door
Chassis	250x150 box section
Axles	125mm Ø 10 stud, 420x180 brakes
Suspension	Mechanical suspension with 75mm wide 4 leaf springs
Tyres	BKT FL693M 560/60Rx22.5 flotation
Tipping Mechanism	Twin 3 stage 4.25" Ø chrome plated tipping rams
Braking	Hydraulic