



Agrotip Silage Press

Model	Width	Wheels	Weight +/-8%
AS-400 GIGA	4.0 m	15	6000 kg
AS-350	3.5 m	13	5000 kg
AS-320	3.2 m	11	4500 kg
AS-300	3.0 m	11	4300 kg
AS-300	3.0 m	9	3900 kg
AS-260	2.6 m	9	3800 kg
AS-210	2.1 m	7	2700 kg



Agrotip Silage Press

The AGROTIP silage compactors are indispensable equipment for all those, who require high-quality silage.

The device will be mounted to the rear/front three-point coupling of a high-performance tractor (170 hp or more, which features a rear boom lifting force of 74 kN (7560 kg).

Silage Press are produced in different widths and with varying number of waggon wheels on the axle shafts. The width varies in between 2.1 m and 4.0 m.

The weight varies in between 2.700 kg to 6.000 kg.

- ▶ The number of train waggon wheels on the axle shafts depend on the width of compactor and increases from 7 to 15 pieces. Every wheel is greased and the axle shaft has inside four grease stacks for excellent daily work
- ▶ The biggest advantage of the machine is, that the two last wheels on the left and on the right side of the compactor overhang and they are not framed by the caning frame of the machine. In this case, the last wheels on both sides, can press silage material directly close to the clamp wall. Excellent for maize & grass stacks with superior consistent compaction.

